

HSS

Shank dia.	Drill dia.	Overall length	Drill length
Ds	Dc	L	ℓ

Size Dc × Ø × Ds	Code	Ds (mm)	Dc (mm)	L (mm)	ℓ (mm)	No. of flutes	TYPE
0.5 × 20° × 6	CS-G0.52-J	6	0.5	57	0.5	2	1
0.5 × 30° × 6	CS-G0.53-J	6	0.5	57	0.5	2	2
0.5 × 20° × 6	CS-G0.52-LS	6	0.5	100	0.5	2	1
0.5 × 30° × 6	CS-G0.53-LS	6	0.5	100	0.5	2	2
0.6 × 20° × 6	CS-G0.62-J	6	0.6	57	0.5	2	1
0.6 × 30° × 6	CS-G0.63-J	6	0.6	57	0.5	2	2
0.6 × 20° × 6	CS-G0.62-LS	6	0.6	100	0.5	2	1
0.6 × 30° × 6	CS-G0.63-LS	6	0.6	100	0.5	2	2
0.7 × 20° × 6	CS-G0.72-J	6	0.7	57	0.5	2	1
0.7 × 30° × 6	CS-G0.73-J	6	0.7	57	0.5	2	2
0.7 × 20° × 6	CS-G0.72-LS	6	0.7	100	0.5	2	1
0.7 × 30° × 6	CS-G0.73-LS	6	0.7	100	0.5	2	2
0.8 × 20° × 6	CS-G0.82-J	6	0.8	57	0.5	2	1
0.8 × 30° × 6	CS-G0.83-J	6	0.8	57	0.5	2	2
0.8 × 20° × 6	CS-G0.82-LS	6	0.8	100	0.5	2	1
0.8 × 30° × 6	CS-G0.83-LS	6	0.8	100	0.5	2	2
0.9 × 20° × 6	CS-G0.92-LS	6	0.9	100	0.5	2	1
0.9 × 30° × 6	CS-G0.93-LS	6	0.9	100	0.5	2	2
1 × 20° × 6	CS-G1.02-J	6	1	57	0.5	2	1
1 × 20° × 8	CS-G1.028J	8	1	57	0.5	2	1
1 × 30° × 6	CS-G1.03-J	6	1	57	0.5	2	2
1 × 30° × 8	CS-G1.038J	8	1	57	0.5	2	2
1 × 20° × 8	CS-G1.028K	8	1	70	0.5	2	1
1 × 30° × 8	CS-G1.038K	8	1	70	0.5	2	2
1 × 20° × 6	CS-G1.02-LS	6	1	100	0.5	2	1
Size Dc × Ø × Ds	Code	Ds (mm)	Dc (mm)	L (mm)	ℓ (mm)	No. of flutes	TYPE
1 × 20° × 8	CS-G1.028LS	8	1	100	0.5	2	1
1 × 30° × 6	CS-G1.03-LS	6	1	100	0.5	2	2
1 × 30° × 8	CS-G1.038LS	8	1	100	0.5	2	2
1.5 × 20° × 8	CS-G1.52-K	8	1.5	70	0.5	2	1
1.5 × 30° × 8	CS-G1.53-K	8	1.5	70	0.5	2	2
1.5 × 20° × 8	CS-G1.52-LS	8	1.5	100	0.5	2	1
1.5 × 30° × 8	CS-G1.53-LS	8	1.5	100	0.5	2	2
2 × 20° × 8	CS-G2.02-K	8	2	70	0.5	2	1
2 × 30° × 8	CS-G2.03-K	8	2	70	0.5	2	2
2 × 20° × 8	CS-G2.02-LS	8	2	100	0.5	2	1
2 × 30° × 8	CS-G2.03-LS	8	2	100	0.5	2	2